

# Astrolite<sup>™</sup>II UNDERWATER LIGHTING

Hayward's AstroLite II series lights offer all the quality, versatility and ease of use you depend on from Hayward, and does so all at a price that gives you the value you expect. AstroLite II series lights feature machine-polished stainless steel face rims, 12 and 120 voltages, and a variety of wattages and cord lengths. Combined with Hayward's Niches, they make an unparalleled value in lighting systems.

# Features-AstroLite<sup>™</sup> II

- Machine polished stainless steel face rim
- E-Z Lock<sup>™</sup> clamp and reflector assembly for simple relamping
- When used with Hayward's SP0601U niche, provides extra space for easy coiling and storage of the relamping cord length
- Blue and red colored lens kit included, offering even greater value

#### Specifications-AstroLite II

- 12 Volt, 75 Watt Halogen
- 120 Volt, 100 Watt Halogen, or 300 Watt Halogen
- 100 % tested for safety and quality assurance
- U.L. Listed (Guide No.WBDT, File No. E39338)

Model	Voltage	Wattage	Lighting	Cord Lengths		
SP0590HSL	12	75	Halogen	15, 30, 50, 75,* 100*		
SP0591HSL	120	100	Halogen	15, 30, 50, 75, 100		
SP0592HSL	120	250	Halogen	15, 30, 50, 75, 100		

\* Hayward does not recommend the installation of 12 Volt lights with cord lengths above 50 feet (voltage available to the light is diminished to a level that significantly reduces light output).

## Features-DuraNiche

- Injection-molded PVC fixture housing for corrosion-free performance
- Socket conduit connection designed for quick and simple gluing to PVC pipe. Provides a cleaner more reliable seal vs. threadedtype connections
- All 1" outlets can quickly be converted to ¾" with UL approved sweep elbow fitting, coupling and reducers (included)
- Easily accessible connections for grounding/bonding
- U.L. Listed and complies with N.E.C. (1993)

#### Specifications-DuraNiche

Model Number	Spa/Pool Type	Conduit Size	Conduit Outlet
SP0601U/SP0601	Gunite/Concrete	1" or ¾ " SKT	45° Rear

## Features-Stainless Steel Niche

- Unibody construction (no front ring)
- No spot welds
- Both large and small niches are available with rear or side mount connnection

- U.L. listed
- Complies with NEC 2002
- Gunite shield can be used to protect the niche or can be reversed to protect the light

#### Specifications-Stainless Steel Niche

Model Number	Spa/Pool Type	Conduit Size	Conduit Outlet
SP0606C/SP0610C Series	Concrete	1⁄2", 3⁄4", 1"	Rear/Side

To take a closer look at Astrolite II or other Hayward products, go to www.haywardpool.com or call 1-888-HAYWARD





Astrolite II Series Lights are listed by:



LITASTROII11