



Tanque: Poly glass / Composite / Fibra de vidrio

Válvula: Flotrol

- Electromecánica
- Digital
- Manual

Material Filtrante: Resina catiónica

TANQUE (TAMAÑO)	TANQUE DE SAL	VOLUMEN (PIE3)	CAPACIDAD MÁXIMA DE GRANOS	FLUJO DE TRABAJO (L.P.M.)	FLUJO DE RETROLAVADO (L.P.M.)	E/S
7"x35"	15"x32"	0.5	15,000	9	5	1"
8"x44"	18"x33"	0.6	22,500	14	6	1"
9"x48"	18"x33"	1	30,000	19	8	1"
10"x54"	18"x33"	1.5	45,000	28	10	1"
12"x52"	18"x40"	2	60,000	38	15	1"
14"x65"	24"x50"	3	90,000	57	19	1"
16"x65"	24"x50"	4	120,000	76	26	1"
18"x65"	24"x50"	5	150,000	77 / 114 / 114	34	1" - 1 1/2" - 2"
21"x62"	24"x50"	7	210,000	82 / 132 / 132	45	1" - 1 1/2" - 2"
24"x72"	24"x50"	10	300,000	83 / 151 / 151	57	1" - 1 1/2" - 2"
30"x72"	30"x50"	15	450,000	86 / 162 / 284	95	1" - 1 1/2" - 2"
36"x72"	48"x60"	20	600,000	313 / 380	132	2" - 3"
42"x72"	50"x60"	30	900,000	321 / 568	189	2" - 3"
48"x72"	50"x60"	40	1,200,000	330 / 750	227	2" - 3"
54"x72"	50"x60"	50	1,500,000	335 / 786	303	2" - 3"
63"x72"	50"x60"	60	1,800,000	243 / 835	379	2" - 3"